

Bolt Down Anti Gawk System

Installation Instructions

Unit Sizes

Panel: Wire Ø 4mm Mesh 50mm x 75mm centres
Overall 1000mm high x 3000mm wide

Product Code: 03-EPCBP, 07-EPPOST

Finish: Pre-galvanized
Mass: 20kg

Slide and Lock Posts:

1000mm – 50mm x 50mm x 1.6mm Product Code:
Type: Black RHS
Finish: Hot dipped galvanized
Mass: 2.5kg

Fixing Flange:

152mm x 152mm x 5mm hot dipped galvanized steel plate.

Fixings

Fixings should conform with AS 4100 for permissible working strength and size of bolts. The recommended fixings are four – 10mm x 75mm Concrete Screw Anchors – we also supply – securely fastening each post fixing flange to the top face of the concrete barrier

Quantities

Allow 2 posts for every panel. Effective cover is 3000mm for panels.

Installation

Two people can easily erect the Bolt Down Anti Gawk System.

Start from an appropriate point on the site and fix the first post through the bottom flange with 4 – 10mm x 75mm Concrete Screw Anchors.

Attach the fence panel to the post using the Slide and Lock assemTMblies. Note the rolled top and bottom of the panel face inside allowing the panel to fit flush against the post.

Attach the other end of the fence panel to a second post. Bolt the second post to the concrete and then tighten the fixings to the flange.

Attach a second panel to the second post as previous and repeat until project is complete.

Important Safety Note:

With the Slide and Lock posts extra security is achieved by locking the latch using self tapping screws in the hole provided at the back of the Slide and Lock assembly.

