

XT BARRIER SYSTEM

INSTRUCTIONS WHEN USING FOR EDGE PROTECTION

Unit Sizes

Panel: Wire Ø 4mm Mesh 50mm
x 50mm centres
Overall 1000mm high x 2400mm wide

Product Code:

Finish: Pre-galvanized
Mass: 13.14 kg

Slide and Lock Posts:

1000mm – 50mm x 50mm x 1.6mm
Product Code:
Type: Black RHS
Finish: Hot dipped galvanized
Mass: 2.5kg

Kickplate:

150mm x 2400mm galvanized sheet,
locked
into the panel

Fixing Flange:

152mm x 152mm x 5mm hot dipped
galvanized steel plate.

Fixings

Fixings should conform with AS 4100 for permissible working strength and size of bolts. The recommended fixings are four – 10mm x 80mm Concrete Screw Anchors – we also supply – securely fastening each post fixing flange to the concrete slab, stairwell, walkway, etc,

Quantities

Allow 1 post for every panel plus one extra post for every corner or end of run. Effective cover is 2400mm for panels.

Installation

Two people can easily erect the Edge Protection Fencing System.

Start from an appropriate point on the site and fix the first post through the bottom flange with 4 – 10mm x 80mm Concrete Screw Anchors with the Slide and Lock assemblies facing into the building.

Attach the fence panel to the post using the Slide and Lock assembly. Note the rolled top and bottom of the panel face inside allowing the panel to fit flush against the post.

Attach the other end of the fence panel to a second post. Bolt the second post to the concrete and then tighten the fixings to the flange.

Attach a second panel to the second post as previous and repeat until project is complete.

Important Safety Note:

With the Slide and Lock posts extra security is achieved by locking the latch using selftapping screws in the hole provided at the back of the Slide and Lock assembly.

FORTRESS FENCING & SAFETY SYSTEMS

PHONE: 1800 809 809 FAX: 1800 980 581 23 Charles St, St Marys NSW
2760

PO Box 700, Kingswood NSW 2747 Email: mail@fortressfencing.com.au