



# Eco-Hoard Technical Drawing



Front View

Side View



Top View



FRONT VIEW




BACK VIEW

# Eco-Panel

## Eco Panel Technical Data

S. NO	Test	Result	Unit	Standard
01	Product	uPVC Eco Sheet		
02	Colour	Off White (Light Grey)		
03	Specific Gravity	1.5 +/-0.05	Gm/cc	ASTM D 792
04	Tensile Strength	331,0	Kg/cm <sup>2</sup>	ASTM D 638
05	Elongation at Break	11	%	ASTM D 638
06	Flexural Strength	622	Kg/cm <sup>2</sup>	ASTM D 790
07	Izod Impact Strength	41	J/M	ASTM D 256
08	Limited Oxygen Index	31	%	ASTM D 2863
09	Hardness (Rockwell)	70		ASTM D 785
10	Long Term Heat Resistance	No Effect		ASTM D 794
11	Heat Distortion Temperature	75	Celsius	ASTM D 648



## Material Safety Data

01	Product Identification	Product Code: LP 400
02	Information on Ingredients	PVC resin homo polymer, Lead free heat stabilizers lubricants, Fibers, Pigments, Impact modifier, UV absorber
03	Hazards Identification	The product is not considered to be a hazardous substance for the environment
04	First Aid Measures	Eye Contact: No Effect Skin Contact: No Effect
05	Handling & Storage	No particular care is required in handling.
06	Disposal Consideration	This product is 100% recyclable and reusable.
07	Transport Information	No dangerous goods according to the regulation.